


適合のニポレックスコンジット：VF・VFS・SR・SRK・FBN・VK・VH・EM形

厚鋼電線管用

薄鋼電線管用


ボックス ストレートコネクタ



呼	形式	d mm	C mm	L mm	CTGおねじ JIS C8305
1/4	RBC-102	8.3	31.9	19	CTG16
3/8	RBC-103	10.6	31.9	20	CTG16
1/2	RBC-104	14.0	33.0	21	CTG16
3/4	RBC-106	19.0	40.7	22	CTG22
1	RBC-108	24.4	47.3	24	CTG28
1 1/4	RBC-110	33.0	58.8	32	CTG36
1 1/2	RBC-112	38.1	67.2	35	CTG42
2	RBC-116	49.4	80.8	39	CTG54
2 1/2	RBC-120	60.1	98.7	46	CTG70
3	RBC-124	75.1	115.5	48	CTG82
3 1/2	RBC-128	84.0	140.0	54	CTG92
4	RBC-132	96.0	156.0	63	CTG104

呼	形式	d mm	C mm	L mm	CTCおねじ JIS C8305
1/4	RBC-102C19(15)	8.3	31.9	19	CTC19(15)
3/8	RBC-103C19(15)	10.6	31.9	20	CTC19(15)
1/2	RBC-104C19	14.0	33.0	21	CTC19
3/4	RBC-106C25	19.0	40.7	22	CTC25
1	RBC-108C31	24.4	47.3	24	CTC31
1 1/4	RBC-110C39	33.0	58.8	32	CTC39
1 1/2	RBC-112C51	38.1	67.2	35	CTC51
2	RBC-116C63(51)	49.4	80.8	39	CTC63(51)
2 1/2	RBC-120C75(63)	60.1	98.7	46	CTC75(63)
3	RBC-124C75	75.1	115.5	48	CTC75


ボックス 45°コネクタ



呼	形式	d mm	C mm	L mm	CTGおねじ JIS C8305
1/4	RBC-202	8.3	27	39	CTG16
3/8	RBC-203	10.6	28	41	CTG16
1/2	RBC-204	14.0	30	42	CTG16
3/4	RBC-206	19.0	31	43	CTG22
1	RBC-208	24.4	38	51	CTG28
1 1/4	RBC-210	33.0	49	66	CTG36
1 1/2	RBC-212	38.1	56	76	CTG42
2	RBC-216	49.4	64	86	CTG54
2 1/2	RBC-220	60.1	79	107	CTG70
3	RBC-224	75.1	92	121	CTG82

呼	形式	d mm	C mm	L mm	CTCおねじ JIS C8305
1/4	RBC-202C19(15)	8.3	27	39	CTC19(15)
3/8	RBC-203C19(15)	10.6	28	41	CTC19(15)
1/2	RBC-204C19	14.0	30	42	CTC19
3/4	RBC-206C25	19.0	31	43	CTC25
1	RBC-208C31	24.4	38	51	CTC31
1 1/4	RBC-210C39	33.0	49	66	CTC39
1 1/2	RBC-212C51	38.1	56	76	CTC51
2	RBC-216C63(51)	49.4	64	86	CTC63(51)
2 1/2	RBC-220C75(63)	60.1	79	107	CTC75(63)
3	RBC-224C75	75.1	92	121	CTC75

ボックス 90°コネクタ



呼	形式	d mm	C mm	L mm	CTGおねじ JIS C8305
1/4	RBC-302	8.3	32	30	CTG16
3/8	RBC-303	10.6	36	34	CTG16
1/2	RBC-304	14.0	37	37	CTG16
3/4	RBC-306	19.0	40	43	CTG22
1	RBC-308	24.4	44	50	CTG28
1 1/4	RBC-310	33.0	57	63	CTG36
1 1/2	RBC-312	38.1	65	71	CTG42
2	RBC-316	49.4	74	86	CTG54
2 1/2	RBC-320	60.1	90	127	CTG70
3	RBC-324	75.1	104	128	CTG82

呼	形式	d mm	C mm	L mm	CTCおねじ JIS C8305
1/4	RBC-302C19(15)	8.3	32	30	CTC19(15)
3/8	RBC-303C19(15)	10.6	36	34	CTC19(15)
1/2	RBC-304C19	14.0	37	37	CTC19
3/4	RBC-306C25	19.0	40	43	CTC25
1	RBC-308C31	24.4	44	50	CTC31
1 1/4	RBC-310C39	33.0	57	63	CTC39
1 1/2	RBC-312C51	38.1	65	71	CTC51
2	RBC-316C63(51)	49.4	74	86	CTC63(51)
2 1/2	RBC-320C75(63)	60.1	90	127	CTC75(63)
3	RBC-324C75	75.1	104	128	CTC75

注記：1. CTG、CTCおねじはJIS C8305厚鋼、薄鋼電線管ねじを示します。
2. 特殊ねじの加工も致します。


仕様は予告なく変更することがありますのでご了承下さい。

適合のニポレックスコンジット：VF・VFS・SR・SRK・FBN・VK・VH・EM 形

厚鋼電線管用

薄鋼電線管用


コンビネーション ストレートコネクタ



呼	形式	d mm	C mm	L mm	CTGめねじ JIS C8305
1/4	RCC-102	8.3	26.4	30	CTG16
3/8	RCC-103	10.6	29.7	31	CTG16
1/2	RCC-104	14.0	33.0	32	CTG16
3/4	RCC-106	19.0	40.7	34	CTG22
1	RCC-108	24.4	47.3	38	CTG28
1 1/4	RCC-110	33.0	58.8	46	CTG36
1 1/2	RCC-112	38.1	67.2	51	CTG42
2	RCC-116	49.4	80.8	55	CTG54
2 1/2	RCC-120	60.1	98.7	66	CTG70
3	RCC-124	75.1	115.5	70	CTG82
3 1/2	RCC-128	84.0	145.0	82	CTG92
4	RCC-132	96.0	157.0	103	CTG104

呼	形式	d mm	C mm	L mm	CTCめねじ JIS C8305
1/4	RCC-102C19(15)	8.3	26.4	19	CTC19(15)
3/8	RCC-103C19(15)	10.6	29.7	20	CTC19(15)
1/2	RCC-104C19	14.0	33.0	21	CTC19
3/4	RCC-106C25	19.0	40.7	22	CTC25
1	RCC-108C31	24.4	47.3	24	CTC31
1 1/4	RCC-110C39	33.0	58.8	32	CTC39
1 1/2	RCC-112C51	38.1	67.2	35	CTC51
2	RCC-116C63(51)	49.4	80.8	39	CTC63(51)
2 1/2	RCC-120C75(63)	60.1	98.7	46	CTC75(63)
3	RCC-124C75	75.1	115.5	48	CT75


コンビネーション 45° コネクタ



呼	形式	d mm	C mm	L mm	CTGめねじ JIS C8305
1/4	RCC-202	8.3	27	51	CTG16
3/8	RCC-203	10.6	28	53	CTG16
1/2	RCC-204	14.0	30	54	CTG16
3/4	RCC-206	19.0	31	55	CTG22
1	RCC-208	24.4	38	65	CTG28
1 1/4	RCC-210	33.0	49	80	CTG36
1 1/2	RCC-212	38.1	56	92	CTG42
2	RCC-216	49.4	64	102	CTG54
2 1/2	RCC-220	60.1	79	127	CTG70
3	RCC-224	75.1	92	143	CTG82

呼	形式	d mm	C mm	L mm	CTCめねじ JIS C8305
1/4	RCC-202C19(15)	8.3	27	51	CTC19(15)
3/8	RCC-203C19(15)	10.6	28	53	CTC19(15)
1/2	RCC-204C19	14.0	30	54	CTC19
3/4	RCC-206C25	19.0	31	55	CTC25
1	RCC-208C31	24.4	38	65	CTC31
1 1/4	RCC-210C39	33.0	49	80	CTC39
1 1/2	RCC-212C51	38.1	56	92	CTC51
2	RCC-216C63(51)	49.4	64	102	CTC63(51)
2 1/2	RCC-220C75(63)	60.1	79	127	CTC75(63)
3	RCC-224C75	75.1	92	143	CTC75

コンビネーション 90° コネクタ



呼	形式	d mm	C mm	L mm	CTGめねじ JIS C8305
1/4	RCC-302	8.3	32	40	CTG16
3/8	RCC-303	10.6	36	44	CTG16
1/2	RCC-304	14.0	37	47	CTG16
3/4	RCC-306	19.0	40	53	CTG22
1	RCC-308	24.4	44	62	CTG28
1 1/4	RCC-310	33.0	57	75	CTG36
1 1/2	RCC-312	38.1	65	85	CTG42
2	RCC-316	49.4	74	100	CTG54
2 1/2	RCC-320	60.1	90	147	CTG70
3	RCC-324	75.1	104	150	CTG82


呼	形式	d mm	C mm	L mm	CTCめねじ JIS C8305
1/4	RCC-302C19(15)	8.3	32	40	CTC19(15)
3/8	RCC-303C19(15)	10.6	36	44	CTC19(15)
1/2	RCC-304C19	14.0	37	47	CTC19
3/4	RCC-306C25	19.0	40	53	CTC25
1	RCC-308C31	24.4	44	62	CTC31
1 1/4	RCC-310C39	33.0	57	75	CTC39
1 1/2	RCC-312C51	38.1	65	85	CTC51
2	RCC-316C63(51)	49.4	74	100	CTC63(51)
2 1/2	RCC-320C75(63)	60.1	90	147	CTC75(63)
3	RCC-324C75	75.1	104	150	CTC75

注記：1. CTG、CTCおねじはJIS C8305厚鋼、薄鋼電線管ねじを示します。
2. 特殊ねじの加工も致します。

仕様は予告なく変更することがありますのでご了承下さい。

適合のニポレックスコンジット：VF・VFS・SR・SRK・FBN・VK・VH・EM 形

テーパーストレートコネクタ




管用テーパースネジ

呼	形式	d mm	C mm	L mm	PTおねじ JIS B2023
1/4	RTC-102	8.3	26.4	19	R 1/2
3/8	RTC-103	10.6	29.7	20	R 1/2
1/2	RTC-104	14.0	33.0	21	R 1/2
3/4	RTC-106	19.0	40.7	22	R 3/4
1	RTC-108	24.4	47.3	24	R 1
1 1/4	RTC-110	33.0	58.8	32	R 1-1/4
1 1/2	RTC-112	38.1	67.2	35	R 1-1/2
2	RTC-116	49.4	80.8	39	R 2
2 1/2	RTC-120	60.1	98.7	46	R 2-1/2
3	RTC-124	75.1	115.5	48	R 3

アメリカテーパースネジ

呼	形式	d mm	C mm	L mm	NPTおねじ ANSI B2.1
1/4	RTC-102NPT	8.3	26.4	19	NPT 1/2
3/8	RTC-103NPT	10.6	29.7	20	NPT 1/2
1/2	RTC-104NPT	14.0	33.0	21	NPT 1/2
3/4	RTC-106NPT	19.0	40.7	22	NPT 3/4
1	RTC-108NPT	24.4	47.3	24	NPT 1
1 1/4	RTC-110NPT	33.0	58.8	32	NPT 1-1/4
1 1/2	RTC-112NPT	38.1	67.2	35	NPT 1-1/2
2	RTC-116NPT	49.4	80.8	39	NPT 2
2 1/2	RTC-120NPT	60.1	98.7	46	NPT 2-1/2
3	RTC-124NPT	75.1	115.5	48	NPT 3


テーパーストレートコネクタ 45° コネクタ



呼	形式	d mm	C mm	L mm	PTおねじ JIS B2023
1/4	RTC-202	8.3	27	51	R 1/2
3/8	RTC-203	10.6	28	52	R 1/2
1/2	RTC-204	14.0	30	54	R 1/2
3/4	RTC-206	19.0	31	55	R 3/4
1	RTC-208	24.4	38	65	R 1
1 1/4	RTC-210	33.0	49	80	R 1-1/4
1 1/2	RTC-212	38.1	56	92	R 1-1/2
2	RTC-216	49.4	64	102	R 2

呼	形式	d mm	C mm	L mm	NPTおねじ ANSI B2.1
1/4	RTC-202NPT	8.3	27	51	NPT 1/2
3/8	RTC-203NPT	10.6	28	52	NPT 1/2
1/2	RTC-204NPT	14.0	30	54	NPT 1/2
3/4	RTC-206NPT	19.0	31	55	NPT 3/4
1	RTC-208NPT	24.4	38	65	NPT 1
1 1/4	RTC-210NPT	33.0	49	80	NPT 1-1/4
1 1/2	RTC-212NPT	38.1	56	92	NPT 1-1/2
2	RTC-216NPT	49.4	64	102	NPT 2

テーパーストレートコネクタ 90° コネクタ



呼	形式	d mm	C mm	L mm	PTおねじ JIS B2023
1/4	RTC-302	8.3	32	44	R 1/2
3/8	RTC-303	10.6	36	47	R 1/2
1/2	RTC-304	14.0	37	51	R 1/2
3/4	RTC-306	19.0	40	58	R 3/4
1	RTC-308	24.4	44	65	R 1
1 1/4	RTC-310	33.0	57	77	R 1-1/4
1 1/2	RTC-312	38.1	65	87	R 1-1/2
2	RTC-316	49.4	74	107	R 2

呼	形式	d mm	C mm	L mm	NPTおねじ ANSI B2.1
1/4	RTC-302NPT	8.3	32	44	NPT 1/2
3/8	RTC-303NPT	10.6	36	47	NPT 1/2
1/2	RTC-304NPT	14.0	37	51	NPT 1/2
3/4	RTC-306NPT	19.0	40	58	NPT 3/4
1	RTC-308NPT	24.4	44	65	NPT 1
1 1/4	RTC-310NPT	33.0	57	77	NPT 1-1/4
1 1/2	RTC-312NPT	38.1	65	87	NPT 1-1/2
2	RTC-316NPT	49.4	74	107	NPT 2

注記：1. R おねじは、JIS B0203管用テーパースネジを示します。NPT は、アメリカテーパースネジを示します。
2. 特殊ねじの加工も致します。

仕様は予告なく変更することがありますのでご了承下さい。